

MSH7-TACH-9VCM2F - Digital Tachometer, Hand Held, Plastic 7.5"x4.1"x1.2", 9V sensor power, 20' CM2 Female Sensor Connection pigtail

MSH7-TACH-9VCM2F, DIGITAL, HAND HELD SCALEABLE TACHOMETER. FEMALE CM2 SENSOR CONNECTOR, 9V BATTERY POWERED.

<p>SENSOR TYPES : HALL EFFECT, MR, FERROUS METAL, & GEAR TOOTH</p>	<p>SENSOR CONNECTION MATES to MALE MS3101A10SL-3P 9V DC POWER TO SENSOR 20' SHIELDED CABLE</p>	<p>OTHER OPTIONS AVAILABLE *CONTACT US FOR QUOTE -WALL MOUNT OPTIONS -OTHER SENSOR CONNECTORS</p>
---	---	--

Our Digital Hand Held Tachometer provides a rate measurement that is determined by the frequency at which an attached digital sensor output is triggering*. The meter can be paired with Hall Effect, Magneto-resistive, Gear Tooth, and Ferrous Metal detection sensors. The displayed rate is scaled based upon customer requirements.

The MSH7-TACH-9VCM2F is a hand-held unit that operates from a 9V battery and provides power to the attached sensor. The included Lithium battery provides 25 or more hours of power to the sensor and meter. An MS Connector on a 20' cable mates to a wide variety of sensors available from Sensor Solutions.

Tachometers can also be provided in a wall mountable or panel mountable enclosures for permanent installation with a variety of connection options. Contact Sensor Solutions to discuss our sensor and meter options and to determine the best complete sensor solution for your application.

*NOTE: Output Trigger is dependent on sensor type. The number of pulses per rotation and operating speeds need to be known for Sensor Solutions to set the display for proper readings. Contact us for details or to determine which sensor and tachometer are best for your application.

SENSOR CONNECTION

